



8 x 8-inch Butyl Adhesive Pads **Installation Procedures**

Pressure sensitive butyl pads are a cost effective solution for temporary installations of Davidson channelizer posts, especially in areas where anchor bolts may not be used, such as parking garages and bridge decks.

- A) A clean, dry surface is required. Sweep or blow off the area where the base will be installed using the broom or blowgun to remove gravel, sand or other debris.
 - B) For optimum performance, the recommended installation temperature is 50 degrees F and rising.
 - C) Special Conditions: All Concrete Surfaces and old Asphalt pavements: prime the surface with DAPCO pavement primer prior to installation of butyl pads
 - D) Remove the slip sheeting from one side of the Butyl Pad and place it on the ground with the exposed adhesive facing up.
 - E) Set the base on the Butyl Pad, centering it within the edges of the pad.
 - F) Step on the base to secure it to the pad. Lift the base and remove the remaining slip sheet from the other side of the pad.
 - G) Place the base/pad assembly in position making sure it is oriented properly. Generally this means the locking pin holes will face oncoming traffic.
 - H) Slowly drive a vehicle up onto the base and stop so one of the front wheels is directly on top of the base. Remain in this position for at least 15 seconds to "set" the adhesive.
 - I) Once the bases are set, install channelizer posts in the bases and lock with 2 pins.
- F) Limitations**
- 1) Insufficient pressure will not allow the adhesive to set. Failure to install correctly can result in loss of the marker and adhesive.
 - 2) Moisture on the roadway will inhibit bonding of the markers. Roadway must be clean and dry prior to installation.
- G) Important Notice to Purchaser**
- The following is made in lieu of all warranties, expressed or implied, including the implied warranties of merchantability and fitness for purpose: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective. Before using, user shall determine the suitability of the product for its intended use, and user assumes all risk and liability whatsoever in connection therewith. Neither manufacturer nor seller shall be liable either in tort or in contract for any loss or damage, direct, incidental, or consequential, arising out of the use of or the inability to use the product.